

# MX Enduro



**Kawasaki**  
Let the Good Times Roll





**KX 450**

## KEY FEATURES

- EVEN STRONGER ENGINE
- SLIM, ERGONOMIC BODYWORK
- LIGHTWEIGHT ALUMINIUM FRAME
- QUICK-RELEASE SIDE COVER
- RACE-READY SUSPENSION
- BREMBO BRAKE SYSTEM



KTRC



SMARTPHONE CONNECTIVITY



LAUNCH CONTROL MODE



ERGO-FIT



POWER MODES



## TECH SPECIFICATIONS

### ENGINE

#### Engine type

Liquid-cooled, 4-stroke, single-cylinder

#### Compression ratio

12.5:1

#### Bore x stroke

96.0 x 62.1 mm

#### Displacement

449 cm<sup>3</sup>

#### Fuel System

Fuel injection: 44 mm x 1

#### Starting system

Electric

### PERFORMANCE & TRANSMISSION

#### Transmission

5-speed, return shift

### FRAME & DIMENSIONS

#### Frame type

Perimeter, aluminium

#### Trail

115 mm

#### L x W x H

2,180 x 820 x 1,270 mm

#### Wheel base

1,480 mm

#### Ground clearance

345 mm

#### Fuel capacity

6.2 litres

#### Seat height

960 mm

#### Curb mass

112,9 kg

### BRAKE & SUSPENSION

#### Front brake type

Single semi-floating petal disc

#### Front brake diameter

Ø 270 mm

#### Front brake caliper type

Brembo dual-piston

#### Rear brake type

Single petal disc

#### Rear brake diameter

Ø 240 mm

#### Rear brake caliper type

Single-piston

#### Front suspension type

Inverted fork with adjustable compression and rebound damping

#### Front suspension diameter

Ø 49 mm

#### Rear suspension type

Uni-Trak, adjustable dual-range (high/low-speed) compression and adjustable rebound damping, and spring preload adjustability



# KX 250



## KEY FEATURES

- SLIM, ERGONOMIC BODYWORK
- ELECTRIC START
- FINE-TUNED SUSPENSION AND BRAKE COMPONENTS
- HYDRAULIC CLUTCH
- LIGHTWEIGHT ALUMINIUM PERIMETER FRAME



KTRC



SMARTPHONE CONNECTIVITY



LAUNCH CONTROL MODE



ERGO-FIT



POWER MODES



## TECH SPECIFICATIONS

### ENGINE

#### Engine type

Liquid-cooled, 4-stroke, single-cylinder

#### Compression ratio

14.0:1

#### Bore x stroke

78.0 x 52.2 mm

#### Displacement

249 cm<sup>3</sup>

#### Fuel system

Fuel injection: 44 mm x 1

#### Starting system

Electric

### PERFORMANCE & TRANSMISSION

#### Transmission

5-speed, return shift

### FRAME & DIMENSIONS

#### Frame type

Perimeter, aluminium

#### Trail

118 mm

#### L x W x H

2,190 x 820 x 1,265 mm

#### Wheel base

1,485 mm

#### Ground clearance

340 mm

#### Fuel capacity

6.2 litres

#### Seat height

955 mm

#### Curb mass

109,5 kg

### BRAKE & SUSPENSION

#### Front brake type

Single semi-floating petal disc

#### Front brake diameter

Ø 270 mm

#### Front brake caliper type

Dual-piston

#### Rear brake type

Single petal disc

#### Rear brake diameter

Ø 240 mm

#### Rear brake caliper type

Single-piston

#### Front suspension type

Inverted fork with adjustable compression and rebound damping

#### Front suspension diameter

Ø 49 mm

#### Rear suspension type

Uni-Trak, adjustable dual-range (high/low-speed) compression and adjustable rebound damping, and spring preload adjustability





**KX 85**

## KEY FEATURES

KX 85 I / KX 85 II

- SLIM ERGONOMICS
- REVISED SHROUD DESIGN
- MULTIPLE SIZE OPTIONS
- FACTORY-INSPIRED STYLING
- INCREASED COOLING PERFORMANCE
- 6-POSITION HANDLEBAR
- STRONGER TRANSMISSION



## TECH SPECIFICATIONS

### ENGINE

**Engine type**

Liquid-cooled, 2-stroke, single-cylinder

**Compression ratio**

10.9:1 (low speed); 9.0:1 (high speed)

**Bore x stroke**

48.5 x 45.8 mm

**Displacement**

84 cm<sup>3</sup>

**Fuel System**

Carburettor

**Starting system**

Primary kick

### PERFORMANCE & TRANSMISSION

**Transmission**

6-speed, return shift

### FRAME & DIMENSIONS

**Frame type**

Perimeter, high-tensile steel

**Trail**

97 mm

**L x W x H**

1,825 x 765 x 1,100 mm

**Wheel base**

1,260 mm

**Ground clearance**

290 mm

**Fuel capacity**

5.0 litres

**Seat height**

830 mm

**Curb mass**

74,6 kg

### BRAKE & SUSPENSION

**Front brake type**

Single petal disc

**Front brake diameter**

Ø 220 mm

**Front brake caliper type**

Dual-piston

**Rear brake type**

Single petal disc

**Rear brake diameter**

Ø 184 mm

**Rear brake caliper type**

Single-piston

**Front suspension type**

Inverted fork with 20-way

compression dampin

**Front suspension diameter**

Ø 36 mm

**Rear suspension type**

Bottom-link Uni-Trak with 24-way

compression and 21-way rebound damping,

and spring preload adjustability





**KX 65**

## KEY FEATURES

- STOP START
- WALK THE WALK
- POWER TO GET YOU STARTED



## TECH SPECIFICATIONS

### ENGINE

**Engine type**  
Liquid-cooled, 2-stroke, single-cylinder  
**Compression ratio**  
8.4:1  
**Bore x stroke**  
44.5 x 41.6 mm  
**Displacement**  
64 cm<sup>3</sup>  
**Fuel System**  
Carburettor  
**Starting system**  
Primary kick

### PERFORMANCE & TRANSMISSION

**Transmission**  
6-speed, return shift

### FRAME & DIMENSIONS

**Frame type**  
Double-cradle, high-tensile steel  
**Trail**  
60 mm  
**L x W x H**  
1,590 x 760 x 955 mm  
**Wheel base**  
1,120 mm  
**Ground clearance**  
305 mm  
**Fuel capacity**  
3.8 litres

**Seat height**  
760 mm  
**Curb mass**  
60 kg

### BRAKE & SUSPENSION

**Front brake type**  
Single disc  
**Front brake diameter**  
Ø 180 mm  
**Front brake caliper type**  
Single-piston  
**Rear brake type**  
Single disc  
**Rear brake diameter**  
Ø 180 mm  
**Rear brake caliper type**  
Single-piston  
**Front suspension type**  
Telescopic fork with 4-way rebound damping  
**Front suspension diameter**  
Ø 33 mm  
**Rear suspension type**  
Bottom-link Uni-Trak, gas-charged shock, stepless rebound damping, and spring preload adjustability





## KEY FEATURES

- EVEN STRONGER ENGINE
- LIGHTWEIGHT ALUMINIUM FRAME
- QUICK-RELEASE SIDE COVER
- BREMBO BRAKE SYSTEM
- CROSS-COUNTRY WHEELS/TYRES
- ESSENTIAL CROSS-COUNTRY EQUIPMENT



KTRC



SMARTPHONE CONNECTIVITY



LAUNCH CONTROL MODE



ERGO-FIT



POWER MODES



## TECH SPECIFICATIONS

### ENGINE

#### Engine type

Liquid-cooled, 4-stroke, single-cylinder

#### Compression ratio

12.5:1

#### Bore x stroke

96.0 x 62.1 mm

#### Displacement

449 cm<sup>3</sup>

#### Fuel System

Fuel injection: 44 mm x 1

#### Starting system

Electric

### PERFORMANCE & TRANSMISSION

#### Transmission

5-speed, return shift

### FRAME & DIMENSIONS

#### Frame type

Perimeter, aluminium

#### Trail

119 mm

#### L x W x H

2,180 x 815 x 1,260 mm

#### Wheel base

1,480 mm

#### Ground clearance

335 mm

#### Fuel capacity

6.2 litres

#### Seat height

955 mm

#### Curb mass

113,8 kg

### BRAKE & SUSPENSION

#### Front brake type

Single semi-floating petal disc

#### Front brake diameter

Ø 270 mm

#### Front brake caliper type

Brembo dual-piston

#### Rear brake type

Single petal disc

#### Rear brake diameter

Ø 240 mm

#### Rear brake caliper type

Single-piston

#### Front suspension type

Inverted fork with adjustable compression and rebound damping

#### Front suspension diameter

Ø 49 mm

#### Rear suspension type

Uni-Trak, adjustable dual-range (high/low-speed) compression and adjustable rebound damping, and spring preload adjustability





**KX 250X**

## KEY FEATURES

- SLIM, ERGONOMIC BODYWORK
- EVEN MORE POWERFUL ENGINE
- ELECTRIC START
- FINE-TUNED SUSPENSION AND BRAKE COMPONENTS
- HYDRAULIC CLUTCH
- LIGHTWEIGHT ALUMINIUM PERIMETER FRAME
- RENTHAL FATBAR



LAUNCH CONTROL MODE



ERGO-FIT



DUAL INJECTORS



## TECH SPECIFICATIONS

### ENGINE

**Engine type**

Liquid-cooled, 4-stroke, single-cylinder

**Compression ratio**

14.0:1

**Bore x stroke**

78.0 x 52.2 mm

**Displacement**

249 cm<sup>3</sup>

**Fuel system**

Fuel injection: 44 mm x 1

**Starting system**

Electric

**Seat height**

950 mm

**Curb mass**

110,6 kg

### BRAKE & SUSPENSION

**Front brake type**

Single semi-floating petal disc

**Front brake diameter**

Ø 270 mm

**Front brake caliper type**

Dual-piston

**Rear brake type**

Single petal disc

**Rear brake diameter**

Ø 240 mm

**Rear brake caliper type**

Single-piston

**Front suspension type**

Inverted fork with adjustable compression and rebound damping

**Front suspension diameter**

Ø 49 mm

**Rear suspension type**

Uni-Trak, adjustable dual-range (high/low-speed) compression and adjustable rebound damping, and spring preload adjustability

### PERFORMANCE & TRANSMISSION

**Transmission**

5-speed, return shift

### FRAME & DIMENSIONS

**Frame type**

Perimeter, aluminium

**Trail**

123 mm

**L x W x H**

2,185 x 820 x 1,260 mm

**Wheel base**

1,485 mm

**Ground clearance**

330 mm

**Fuel capacity**

6.2 litres





**KLX 230R**

## KEY FEATURES

- SCAPABLE OFF-ROAD PERFORMANCE
- COMPACT, LIGHTWEIGHT, MANOEUVRABLE
- LARGER CAPACITY FUEL TANK
- REVISED SEAT
- CONTROLLABLE RIDING POSITION
- LATEST KX STYLING WITH SMOOTH-DESIGN BODYWORK
- 233 CM3 FUEL-INJECTED ENGINE WITH IMPROVED LOW-MID RANGE & BALANCER
- LONG-TRAVEL SUSPENSION WITH LARGE-DIAMETER 21"/18" WHEELS



ERGO-FIT



## TECH SPECIFICATIONS

### ENGINE

**Engine type**  
Air-cooled, 4-stroke, single-cylinder  
**Compression ratio**  
9.4:1  
**Bore x stroke**  
67.0 x 66.0 mm  
**Displacement**  
233 cm<sup>3</sup>  
**Fuel system**  
Fuel injection: 32 mm x 1  
**Starting system**  
Electric

### PERFORMANCE & TRANSMISSION

**Transmission**  
6-speed, return shift

### FRAME & DIMENSIONS

**Frame type**  
Tubular, semi-double cradle  
**Trail**  
100 mm  
**L x W x H**  
2,035 x 845 x 1,185 mm  
**Wheel base**  
1,355 mm  
**Ground clearance**  
270 mm  
**Fuel capacity**  
7.6 litres

**Seat height**  
875 mm  
**Curb mass**  
184 kg

### BRAKE & SUSPENSION

**Front brake type**  
Single disc  
**Front brake diameter**  
Ø 240 mm  
**Front brake caliper type**  
Dual-piston  
**Rear brake type**  
Single disc  
**Rear brake diameter**  
Ø 220 mm  
**Rear brake caliper type**  
Single-piston  
**Front suspension type**  
Telescopic fork  
**Front suspension diameter**  
Ø 37 mm  
**Rear suspension type**  
New Uni Trak with adjustable preload



# **Kawasaki**

Let the Good Times Roll